Gigaset R700H protect PRO

Created to enable your business under challenging conditions and to protect your employees anytime, anywhere!

Highlights

- o 2.4" TFT colour display
- Motion sensor for will independent alarm scenarios such as man down alarm, no movement alarm and escape alarm
- Red "SOS" alarm key with domed shape for easier keypress that can even be operated with gloves
- Time alarm: User is prompted to react at specific times
- Technical alarm: Detects local technical faults, sends keep-alive requests
- Different alarm modes: Basic (Call based), Alarm and PNG (both via MQTT API interface)
- Torch LED to indicate an alarm, to better find the person in case of an accident
- Alarm, Messaging and Location (AML) support: Alarm call is sent via
 MQTT protocol or via a call to the alarm server
- o IP65: Protected against dust, metal dust and water jets
- Bluetooth/BLE: Bluetooth beacon and beacon scan to locate the position in case of emergency



The Gigaset R700H protect PRO is the rugged handset from Gigaset that is perfectly equipped for a wide variety of alerting and lone worker scenarios. With its motion sensor, it can detect various automatic alarm scenarios. For manual alarm triggering, it is equipped with a red, domed "SOS" alarm button that is easy to press even when wearing gloves. A notification terminal with icon set for various alarm scenarios, a Bluetooth beacon scan function and an integrated torch LED round off the alarm features.

Alarm, Messaging, Location - Protect your employees

The Gigaset R700H protect PRO is equipped with a motion sensor so it can detect various will-independent alarm types including man down alarm. Therefore it is entitled to be certified for lone worker scenarios (i.e. German DGUV 112-139). It has a programmable red function key with a domed shaped that can easily be pressed even with working gloves in case of manual alarm triggering. An AML messaging terminal and icon set, Bluetooth beacon functionality, integrated torch LED and bi-color LED for Message Waiting Indication (MWI) with status indication complete the set of useful alarming features.

Robustness - cope with challenging conditions

In addition to the rubberized surface which gives the device a perfect grip the new R700H protect PRO is designed in such a way that it can also be operated with work gloves. The display glass is proof against scratches thanks to a harder surface and can therefore be used in extreme working environments. With an IP65 certification, the R700H protect PRO is protected against the ingress of dust and water jets. In addition, the special magnetic shielding makes the R700H protect PRO resistant to metal dust. The handset has a disinfectant-resistant surface, which simplifies cleaning and thus protects against bacteria and virucides.

Business functions and smart security gadgets

The Gigaset R700H protect PRO scores in the professional environment with its large 2.4" TFT colour display and a wide range of business functions such as SUOTA, Bluetooth, a brilliant sound quality and vibration alert. Optimized for Gigaset single and multi-cells and for use behind alarm systems. Via autoprovisioning the administrator can configure a larger number of handsets remotely. Upload phonebook entries, preset all relevant settings as well as upload and assign ringtones for consistent sound experience.



Technical Specifications

Ordering Information	Colour	black		
	Functions	 Display keys for quick selection of functions Side button for easy volume control Alarm button Key protection on/off via # key with PIN protection Key lock with PIN protection - Start an alarm despite PIN protection 		
Keyboard	Key type	Illuminated, scratch-resistant and easy-to-clean keyboard pad		
Reyboard	Keys	 Profile key to apply personal, silent and loud settings directly 5-way navigation key Message key with flashing LED R key Mute key 10 number keys 		
	T			
Audio	Audio quality	 HD audio with HDSP™/CAT -IQ 2.1 Handsfree talking on the handset in best acoustic quality 		
Audio	Acoustic profiles	Selectable audio profile (personal, DND, quiet and loud)		
	Volume	5 volume levels / OFF / crescendo adjustable		
	Address book	 Address book for up to 500 entries (vCards) Contacts: First name, last name, 3 phone numbers, email, anniversary, VIP melody, photo for Picture CLIP. 		
Phone book	Contacts	PBX phone book with search function (XML, XSI and LDAP)		
	Phone book transfer	Phone book via Bluetooth $^{\!@}\!\!:$ search, select and download contacts from smartphone		
	General	Vibration alarm		
	CLID	News Info (MWI) Called indication displayed via CLIB mixture CLIB and CNIB.		
Signalling & display indications	CLIP Ringtones	 Caller indication displayed via CLIP, picture CLIP and CNIP 32 Ringtones / melodies Individual ringer melodies for VIP entries and internal callers as we as corresponding alerting scenarios with priority levels 		
	Missed call	 Display and flashing message key signal missed calls and provide convenient access to the message list (LED flashing can be switched on / off) List showing up to 20 missed calls with caller indication 		
	Indicator tones	Tones for leaving and re-entering the DECT radio range		
	Screen saver	Screensaver (picture, slide show, clock, info service)		
	Incoming calls	Spot LED as torch and for call signalling		
Service	xHTML (RAP) services	VoIP platform features: DND, Call Divert, Phonebook, Logon / Logoff, Other services		
Display	Size (inch)	2.4"		
	Resolution	240 x 320 Pixel		
	Туре	TFT colour display		
	Lighting	Amber		
	Colours	64 Thousand		
	1			
Power supply	Talk time	Up to 13 hours		
	Stand-by time	Up to 300 hours		
	Charging compatibility Battery	Charging even when switched off 2 x AAA (NiMH)		



	Di atauti 44		
luetooth connection	 Bluetooth 4.1 Bluetooth Low Energy (BLE) with Bluetooth Beacon and Beacon Scan functionality 		
eadset connection	Headset via Bluetooth® or 3.5 mm jack		
SB ports	Connection to PC via micro USB		
tandards	 DECT GAP DECT-CAT-iq 2.1 (handset) SUOTA (Software update over the air) 		
igaset products	Full compatibility with the professional Gigaset DECT single and multi-cell systems (N610 IP PRO, N670 IP PRO, N870 IP PRO, N870E IP PRO)		
larm, Messaging and ocation (AML)	 Automated alarms: man down, no motion and escape alarm Technical alarms: Battery level / DECT signal / Keepalive Time alarm: User is prompted to respond at specific times Alarm key "SOS" (Single / Multi / Longpress) The alarm call is sent to the alarm server via the MQTT protocol or a call Configurable pre-alarm: Time, melody, volume Configurable alarm: Time, melody, volume Pause in/out of charger Automatic logon from charger Message transmission: Acoustic and visual message signaling depending on priority Message icons: 21 in 5 colors Storage of missed alarm messages Indication of monitoring and protection status by LED Transmission of location data to the alarm server (DECT & Bluetooth) Setting the alarm mode (Basic, Alarm, PNG) 		
alondar	Organiser with calendar and reminder functions		
aiciidai	Organisci with calendar and reminder functions		
	Durate ation along IDCE		
urface durability	Protection class IP65 Disinfectant resistant, scratch resistant and protected against metal dust		
perating temperature	+5 °C to 45 °C ambient temperature		
perating humidity	Relative humidity between 20% and 75%, non-condensing		
egulations <i>l</i> pecifications	-15°C to +65°C		
edial	Automatic redial Redialling the last 20 numbers		
doore	Lin to E0 m		
	Up to 50 m		
นเนบบาร	Up to 300 m		
	3 separate call lists (missed/incoming/outgoing) with 20 entries with CLIP/CNIP and time/date		
aller list	Locally managed list of missed calls on GAP systems (single/multicell systems) Direct dialling from the list of missed calls		
	eadset connection SB ports andards igaset products alendar rotection class urface durability perating temperature perating humidity egulations / pecifications		



App / Web App	Gigaset QuickSync	 Address book synchronisation via QuickSync (Outlook, Google contacts) Upload CLIP images / screensaver images Transferring sounds (ringing melodies) from the computer to the handset Firmware update
	Computer Telephony Integration (uaCSTA)	 Direct dialling from your computer Display of incoming calls on the computer - for Windows and OSX
	Reduction of energy	Up to 60% less energy consumption due to energy-saving power
ECO-DECT	consumption	supply unit
	Reduction of the transmitting power	 ECO mode - Manual reduction of the transmitting power of the base station and all registered handsets Variable reduction of transmission power depending on the distance between handset and base station (handset only)
Network specifications	Provisioning	 Remote bulk configuration by administrator to efficiently prepare handsets for deployment Settings (e.g. display keys, alarm key, emergency numbers) Menus, e.g. settings - Hide to protect against accidental changes Upload the phone book Upload ringtones, assignment and volume

Dimensions 9	Device	Height	Width	Depth	Weight
	Handset	159 mm	54 mm	25 mm	126 g
Dimensions & Weights	Charging cradle	75 mm	74 mm	44 mm	123 g
Weights	Handset incl. charging cradle	168 mm	75 mm	76 mm	249 g

• Upload images

	1x	Handset
	2x	AAA rechargeable batteries
Scope Of Delivery	1x	Beltclip
	1x	Charging cradle
	1x	Security Leaflet

Herausgegeben von Gigaset Communications GmbH. Alle Rechte, Liefermöglichkeiten und Änderungen in Technik und Design vorbehalten. Die in diesem Dokument verwendeten Produktnamen sind Warenzeichen oder eingetragene Warenzeichen ihrer jeweiligen Inhaber. ProDSION-DE-0221

Version 25.10.2023

