

# N870

## Introduction

### N870 Multicell system:

- Up to 250 users / SIP accounts / DECT handsets
- 1 to 60 base stations
- Up to 10 simultaneous G.711 calls per base (8 G.729 Calls or 5 G.722 Calls)
- Seamless handover and roaming
- Ethernet RJ45 10/100 Mbps
- Integrated power over Ethernet
- Wall mountable
- One hardware which can be switched to roles: Integrator / DECT Manager / DECT Base

### With Virtual Integrator

- Up to 20000 users / SIP accounts / DECT handsets
- Up to 6000 base stations

### Software:

- Up to 60 parallel calls per N870 Multicell system
- Exceptional HD sound with HDSP
- DECT latest security standard
- Security: TLS, SRTP, SIPS, HTTPS
- Easy setup and configuration
- LDAP(S) Directories (up to 10)
- XML Directories
- Auto-provisioning
- IPUI based handset registration
- Sync over the air (DECT) and Sync over LAN (PTPv2), also mixed
- Firmware update, file based, scheduled

**S**  
**m**  
**a**  
**i**  
**l**  
**l**  
**s**  
**y**  
**s**  
**t**  
**e**  
**m**  
1-  
10  
ba  
se  
-  
st  
ati  
on  
s,  
50  
ha  
nd  
se  
ts  
an  
d  
10  
si



multaneous calls. (DECT manager is also a DECT base and in this mode it supports 5 concurrent calls)

**Medium system:** 11-60 base-stations, 250 handsets and 60 simultaneous calls. (Due to capacity, DECT manager is only a manager. Switching between Medium and Small is costing you one additional device.)

**Large system:** Up to 240 base-stations, 800 handsets and 240 simultaneous calls. N870 in [role integrator only](#) is needed.

**Enterprise system:** Up to 6000 base-stations, 20000 handsets and 6000 simultaneous calls. [Virtual Integrator](#) is needed.



Firmware



Manual



FAQ



Datasheet



Interop

DECT

Handsets



