

Interop IP devices Voys



Standard
Interop

Voys

Over Voys

Zorgen dat jouw bedrijf kan bellen en bereikbaar is voor jouw klanten. Dat is wat Voys doet, maar dan op een unieke manier. Bij alles wat we doen kijken we of het slimmer, beter en vriendelijker kan. Zo bieden we de communicatieoplossing waar we zelf gelukkig van worden, geleverd door een bedrijf waar we met plezier werken.

Documentation and information:

Find [here](#) the support page

See below for a list with supported features when using the Gigaset PRO IP Devices on the providers network.



Supported features

Feature	Maxwell 3	Maxwell 2	Maxwell basic	N870	N720	N510	DE310	DE700
				IP	IP	IP	/ DE410 IP	/ DE900 IP
Software release:	2.25.6	2.25.6	2.25.6	2.16.2	112	248	02.00.03	02.00.06
Basic Call	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Calling line (CLIP)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Connected line (COLP)	_1	_1	_1	_1	_1	_1	_1	_1
Anonymous call	_2	_2	_2	_2	_2	_2	_2	_2
Do Not Disturb	Yes	Yes	Yes	Yes	-	-	Yes	Yes
Message waiting	_1	_1	_1	_1	_1	_1	_1	_1
Call list/history	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Voice mail deposit/retrieval	_1	_1	_1	_1	_1	_1	_1	_1
Call waiting	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Call Hold / Toggle	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Call forward (CFU)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Call forward (CFNR)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Call forward (CFB)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Call Transfer attended	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Call Transfer early attended	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Call Transfer unattended	Yes	Yes	Yes	Yes	-	-	Yes	Yes
Call completed elsewhere	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
DTMF (RFC2833/4733)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Conference 3pty	Yes	Yes	Yes	_4	-	Yes	Yes	Yes
BLF Busy / Idle indication	Yes	Yes	Yes ³	-	-	-	_1	_1
Call pick-up direct	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Call pick-up group	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Call pick-up BLF	Yes	Yes	Yes ³	-	-	-	_1	_1
Auto provisioning	Yes	Yes	Yes		_1	Yes	_1	_1
TCP	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

-	Not supported by device
_1	Not supported by the platform
_2	Platform feature via FAC
3	Via key extention module
_4	Will be added via firmware update