

N670

Introduction

N670 Single Cell / [Mini-multicell](#) system:

- Up to 20 users / SIP accounts / DECT handsets
- As Single Cell with 1 device with the role all in one
- Add up to 2 N670 device's with the role base station only, to create a Mini-multicell
- Up to 8 simultaneous G.711/ G.729 calls per base (5 G. 722 Calls)
- Ethernet RJ45 10/100 Mbps
- Integrated power over Ethernet
- Wall mountable

Central Management

- Central management of N670 in different locations by N870 Virtual Integrator software*
- One hardware, which can be switched from role
 - Integrator + DECT Manager + DECT Base
 - DECT Manager + DECT Base
 - DECT Base

Upgrade to N870 multi cell functionality

- [License upgrade](#)

Software:

- Up to 8 parallel calls
- Exceptional HD sound with HDSP
- DECT latest security standard
- Security: TLS, SRTP, SIPS, HTTPS
- Easy setup and configuration
- LDAP(S) Directories (up to 10)
- Central directory hosted by N670
- XML directories
- Auto-provisioning
- IPUI based handset registration
- Firmware update, file based, scheduled
- uaCSTA support for CTI-integration
- XHTML applications by customer



Firmware



Manual



FAQ



Datasheet



Interop



Handsets