

# LDAP Provisioning Parameter - N510 IP PRO

**This is list of fields used to store LDAP attributes (with default values) needed for provisioning:**

```
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[0].aucItemAttribute[0]="givenName"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[1].aucItemAttribute[0]="sn"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[2].aucItemAttribute[0]="homePhone"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[3].aucItemAttribute[0]="telephoneNumber"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[4].aucItemAttribute[0]="mobile"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[5].aucItemAttribute[0]="mail"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[6].aucItemAttribute[0]="facsimileTelephoneNumber"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[7].aucItemAttribute[0]="company"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[8].aucItemAttribute[0]="street"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[9].aucItemAttribute[0]="l"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[10].aucItemAttribute[0]="postalCode"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[11].aucItemAttribute[0]="c"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[12].aucItemAttribute[0]=""
```

**Order of items is:**

FIRST NAME,  
LAST NAME,  
PHONE HOME,  
PHONE OFFICE,  
PHONE MOBILE,  
EMAIL,  
FAX,  
COMPANY,  
STREET,  
CITY,  
ZIP,  
COUNTRY,  
ADDITIONAL ATTRIBUTE

**For last item there's also an additional field:**

```
BS_LDAP_Netdirs.astNetdirProvider[%].IsAdditionalAttributeDialable=[0|1]
```

This can be used to indicate that additional attribute should be treated as diallable number.

**Enable the LDAP directory:**

```
<SYMB_ITEM ID="BS_XML_Netdirs.aucActivatedNetdirs" class="symb_item" value="10"/>
```