

# FAQ T640 T440 FAX

## Introduction

The T640/T440 has an integrated fax server that can be used for receiving incoming fax and send outgoing fax.

Incoming fax is converted to a pdf file.



### Important

T38 FAX protocol is needed to provide a reliable FAX transmission. Please check if your provider supports T.38

## Settings

Go to:

**Administration - System - Fax**

Enable the Fax service.

**Fax prefix incoming:** Defines the numbering of the users fax internal numbers:  
Example: User 206 has fax number 9206. With the incoming routing rules, the external numbers can be forwarded to the internal fax numbers.

A **Transmitting Subscriber Identification (abbreviated TSI)** is a number that identifies a specific fax machine as the sender of a fax transmission. The transmitting machine sends its TSI to the receiving machine. The receiving machine typically prints the TSI at the top or bottom of the received fax to help the recipient determine the fax's origin.

**TSI prefix (outgoing):** Define the TSI for the users fax numbers, the system will add the internal fax number of the user.

**Additional TSI's:** Define the global TSI for the system, when selected this number will not be changed, like with the TSI prefix (outgoing)

## Send fax

The user can send a fax via the user web-interface and using an pdf file. Only pdf files can be send and other document types have to be converted to pdf first.

Menu
Administration

Outgoing
Received
Send fax
Sent

Data on this page belong to user: 206

Send Fax

Transmitting subscriber ID

0049 211 5205 56206

Recipient fax number

0049 211 5205 56206

0049 211 5205 5100

File

Resolution

Medium resolution: 98 lpi

### Transmitting subscriber ID:

Select the TSI that is send to the receiving machine. You can choose from your own TSI or from the Additional TSI. You see that you own TSI is compiled from:

**TSI prefix (outgoing) + own number**

**Recipient fax number:** The Fax number where to send the fax.

**File:** The pdf file

**Resolution:** The required fax resolution.



### Important

The TSI should only contain numbers, if it contains characters then the system will not send out the fax.

## Outgoing

Overview of all pending fax transmissions.

Outgoing

Received

Send fax

Sent

Outgoing

Date	Recipient	Job	Pages	Resolution	Attempts	Error
18.12.14 15:16:35	9206	8	0 / 3	98 lpi	0	

## Received

Overview of all received fax transmissions.


Outgoing

Received

Send fax

Sent

Received

Date	Sender	Duration	Size	Pages	Resolution	Speed		
18.12.14 15:17:59	0049 211 5205 5100	0:01:08	85 kb	3	98 lpi	14400 bps	View	

Click on **View** to open the PDF

## Sent

Overview of all finished fax transmissions.

Sent

Date	Recipient	Job	Pages	Resolution	Attempts	Error
17.12.14 13:16:26	004921152055100	7	0 / 1	98 lpi	1	Job aborted by re

- [Introduction](#)
- [Settings](#)
- [Send fax](#)
- [Outgoing](#)
- [Received](#)
- [Sent](#)