

FAQ T640 T440 FAX

Introduction

The T640/T440 has an integrated fax server that can be used for receiving incoming fax and sending outgoing fax.

Incoming fax is converted to a pdf file.



Important

T38 FAX protocol is needed to provide a reliable FAX transmission. Please check if your provider supports T.38

Settings

Go to:

Administration - System - Fax

Enable the Fax service.

Fax prefix incoming: Defines the numbering of the users fax internal numbers: Example: User 206 has fax number 9206. With the incoming routing rules, the external numbers can be forwarded to the internal fax numbers.

A **Transmitting Subscriber Identification (abbreviated TSI)** is a number that identifies a specific fax machine as the sender of a fax transmission. The transmitting machine sends its TSI to the receiving machine. The receiving machine typically prints the TSI at the top or bottom of the received fax to help the recipient determine the fax's origin.

TSI prefix (outgoing): Define the TSI for the users fax numbers, the system will add the internal fax number of the user.

Additional TSI's: Define the global TSI for the system, when selected this number will not be changed, like with the TSI prefix (outgoing)

Send fax

The user can send a fax via the user web-interface and using a pdf file. Only pdf files can be sent and other document types have to be converted to pdf first.

Transmitting subscriber ID: Select the TSI that is sent to the receiving machine. You can choose from your own TSI or from the Additional TSI. You see that your own TSI is compiled from:

TSI prefix (outgoing) + own number

Recipient fax number: The Fax number where to send the fax.

omeMenuAdministration

cts

sts

Forwarding

or

es

Settings

OutgoingReceivedSend faxSent

Data on this page belong to user: 206

Send Fax

Transmitting subscriber ID

0049 211 5205 56206

Recipient fax number

0049 211 5205 562060049 211 5205 5100

File

Resolution

Medium resolution: 98 lpi

File:
The pdf file

Resolution: The required fax resolution.

i

Important
The TSI should only contain numbers, if it contains characters then the system will not send out the fax.

Outgoing

Overview of all pending fax transmissions.

OutgoingReceivedSend faxSent

Outgoing

Date	Recipient	Job	Pages	Resolution	Attempts	Error
18.12.14 15:16:35	9206	8	0 / 3	98 lpi	0	

Received

Overview of all received fax transmissions.

OutgoingReceivedSend faxSent

Received

Date	Sender	Duration	Size	Pages	Resolution	Speed		
18.12.14 15:17:59	0049 211 5205 5100	0:01:08	85 kb	3	98 lpi	14400 bps	<div>View</div>	<div></div>

Click on **View** to open the PDF

Sent

Overview of all finished fax transmissions.

OutgoingReceivedSend faxSent

Sent

Date	Recipient	Job	Pages	Resolution	Attempts	Error
17.12.14 13:16:26	004921152055100	7	0 / 1	98 lpi	1	Job aborted by request

- [Introduction](#)
- [Settings](#)
- [Send fax](#)
- [Outgoing](#)
- [Received](#)

- Sent