

FAQ T640 T440 System settings - Firmware update DE... devices

Introduction

In the administrator web-interface: **Administration - System - Systems settings - Provisioning** you have the option "**Firmware update DE... devices**"

Firmware update DE... devices	<input type="checkbox"/> OFF	<input checked="" type="checkbox"/> <input type="checkbox"/>	Enable automatic firmware update for DE... devices
DE310 firmware version	<input type="text" value="02.00.11"/>	<input checked="" type="checkbox"/> <input type="checkbox"/>	Define the required Gigaset DE310 firmware version
DE410 firmware version	<input type="text" value="02.00.11"/>	<input checked="" type="checkbox"/> <input type="checkbox"/>	Define the required Gigaset DE410 firmware version
DE700 firmware version	<input type="text" value="02.00.15"/>	<input checked="" type="checkbox"/> <input type="checkbox"/>	Define the required Gigaset DE700 firmware version
DE900 firmware version	<input type="text" value="02.00.15"/>	<input checked="" type="checkbox"/> <input type="checkbox"/>	Define the required Gigaset DE900 firmware version

Here you can disable/enable the automatic firmware update for the Gigaset DE... devices.

- DE900/700
- DE410/310

When firmware update is enabled, the system will upgrade the devices to the defined firmware version in the list. You can change the firmware version if a newer firmware is available.

The new firmware needs to be uploaded on the harddrive of the PBX.

By default the system will upgrade the DE... devices via tftp protocol.

The firmware update will start:

- After reboot
- After time, by default during the night between 2 and 6 o'clock.

- [Introduction](#)