

FAQ N510 Bin file provisioning

Introduction

For bin file provisioning, the tool that converts the XML file to bin file has to be installed on a Linux server.

XML files are used

- As direct input (plain XML provisioning) for Gigaset VoIP phones or
- As input for the `gigaset_profile_gen` application which converts the configuration into a binary format comprehensible for Gigaset VoIP phones

The `gigaset_profile_gen` application

The `gigaset_profile_gen` is a console application intended to be called from a CGI script that converts the XML to a secure "bin" file.

Synopsis

```
gigaset_profile_gen XML_INPUT_FILE OUTPUT_FILE [-s] [-noencrypt]
```

Description

Generates the encrypted configuration file from the given `XML_INPUT_FILE` and places it in `OUTPUT_FILE`.

Mandatory arguments

`XML_INPUT_FILE` File containing the configuration data for the phone to be provisioned

`OUTPUT_FILE` Binary, encrypted version of the configuration, ready to be sent to the phone.

Optional arguments

-s Silent operation: suppresses any output by the program to STDOUT; when called from a CGI application, this argument must be used, because the CGI standard uses STDOUT to gather the response that HTTP will send to the client. Without this parameter, the HTTP response would contain unwanted text, such as the sign-on message generated by the program!

-noencrypt Don't encrypt the output file This argument must only be used if the phone does not require.

Remarks

- In order to encrypt the configuration file, `gigaset_profile_gen` usually needs a secret key, which is contained in a file named `key`. This file must be located in the same directory as the application. The secret key must coincide with the one used in the phone. Therefore, the key file is customised by Gigaset for the provisioner. In certain closed network scenarios, the provisioner might desire to work with an unencrypted configuration file. In this case, the phone has to be customised by Gigaset accordingly ("no secret key"), and the argument `-noencrypt` shown above must be given when invoking the `gigaset_profile_gen` application for building the file. Note that for security reasons Gigaset recommends using encrypted configuration files only.
- To make sure that the `XML_INPUT_FILE` contains only configuration parameters the phone understands, the `gigaset_profile_gen` validates it against a fixed schema file (referred to inside the XML file). This schema file is provided by the Gigaset. It must be located in the same directory as the `XML_INPUT_FILE`.

If the validation fails, the application returns an error.

Return values

`gigaset_profile_gen` returns 0 on success. All other values indicate an error. Error messages are sent to STDERR. In the case of errors, an empty `OUTPUT_FILE` is generated.

`gigaset_profile_gen` version 2.6

- Created for N510
- Version Value field is now optional

[Download](#)

- [Introduction](#)
- [The gigaset_profile_gen application](#)
 - [Synopsis](#)
 - [Description](#)
 - [Mandatory arguments](#)
 - [Optional arguments](#)
 - [Return values](#)
- [gigaset_profile_gen version 2.6](#)