

FAQ Distinctive Ringing protocol

Introduction

Distinctive Ring offers the possibility to use different ringtones for Internal, external or group calls.

Distinctive ringing is implemented in:

- DE700/900 Release 02.00.05 or higher
- DE310/410 Release 02.00.02 or higher
- N510 Software 236 or higher (**Support for Alert-info Internal ringtone, all others are played as external ringtones.**)
- N720 Software 99 or higher (**Support for Alert-info Internal ringtone, all others are played as external ringtones.**)
- Maxwell 10
- Maxwell 3 and Basic

The Platform / provider has to send the correct information using the *Alert-Info: Header*.

Distinctive Ringing protocol

PBX sends URI of a ring melody in SIP 'Alert-Info' header field in the following format:

Alert-Info: <URI>[;<RINGER_INFO>[;<POSTFIX>]]

[] – includes optional parameters

<URI>

URI of the ringer melody. If a special (configurable) URI is used, e.g.: <http://www.example.com>, or <http://127.0.0.1>

then it means for the phone that Alert-Info contains local ring melody tag, otherwise URI points at a ringer melody (in .wav format) in the network, which shall be downloaded and played by the phone.

<RINGER_INFO>

Tag of internal ringer melody in the form *<info=TAG>*. TAG is configured via phone's Web UI.

<POSTFIX>

Groupcall:

Alert-Info: <http://www.example.com>;info=alert-group

Internal call:

Alert-Info: <http://www.example.com>;info=alert-internal

In the N510 and N720, there is a new provisioning parameter that provides a limited functionality to change the Alert-Header:

BS_VOIP_Data.aucS_SIPAlertInfoHeaderInternal[0]="alert-internal"

External call:

Alert-Info: <http://www.example.com>;info=alert-external

N510 / N720 how to select the Internal / External ringtone.

Ringtones can only be changed in the DECT handset, there is no web-interface to change the ringtones.

On the handset go to: **Menu - Settings - Audio Settings - Ringtones (Handset) - Melodies**

- Internal Calls: (The ringtone when the Internal Alert Header is received and recognized)
- Tones for the different SIP accounts. (Ringtone used when it is not an Internal Ringtone)

Example header send to N510 behind Gigaset T440/T640

Alert-Info: <http://www.notused.com>;info=alert-internal

There are 2 possibilities to enable distinctive ring on the Gigaset T300/T500.

- [Using a module](#)
- Manual (See below)

In the Gigaset T300/T500 you can enable distinctive ringing by changing the Manual configuration of the line settings, like the example below.

The screenshot shows the configuration interface for a Gigaset T300/T500. On the left is a sidebar with navigation options: Lines, Routing, Server, Statistic, Interconnection, Security, and Extended Settings. The 'Lines' tab is selected. The main area shows configuration for a line with prefix '***'. Under the 'Manual Configuration' section, which is active, the following configuration is shown:

```
[X2COM-incoming]
exten => _,1,Set(channelname=X2COM-incoming)
exten => _,2,Set(lineconfigid=1946)
exten => _,3,SIPAddHeader(Alert-Info: <http://127.0.0.1>;info=alert-external)
exten => _,4,Goto(X2COM-incoming-manuell,${EXTEN},1)

[X2COM-incoming-manuell]
exten => _X.,1,Goto(incoming,${EXTEN},1)
```

Here we added the line:

```
exten => _,3,SIPAddHeader(Alert-Info: <http://127.0.0.1>;info=alert-external)
```

This causes that for every incoming external call, the Alert-Info header is added and the device now can react on this using a special ringtone.

How to work with groups you can see below.

We changed the incoming dialplan so that when a call for the group with number: 31859020520 is coming in, the Alert-Info field is changed to alert-group.

```
[X2COM-incoming]
exten => 31859020520,1,Set(channelname=X2COM-incoming)
exten => 31859020520,2,Set(lineconfigid=1946)
exten => 31859020520,3,SIPAddHeader(Alert-Info: <http://127.0.0.1>;info=alert-group)
exten => 31859020520,4,Goto(X2COM-incoming-manuell,${EXTEN},1)
```

```
exten => _,1,Set(channelname=X2COM-incoming)
exten => _,2,Set(lineconfigid=1946)
exten => _,3,SIPAddHeader(Alert-Info: <http://127.0.0.1>;info=alert-external)
exten => _,4,Goto(X2COM-incoming-manuell,${EXTEN},1)
```

```
[X2COM-incoming-manuell]
exten => _X.,1,Goto(incoming,${EXTEN},1)
exten => _+X.,1,Goto(incoming,${EXTEN},1)
```

The Hybrid 120 GE already sends the correct Alert header, no programming is needed.

- [Introduction](#)
- [Distinctive Ringing protocol](#)
 - [Groupcall:](#)
 - [Internal call:](#)
 - [External call:](#)
- [N510 / N720 how to select the Internal / External ringtone.](#)

