# LocaPhone VoIP PBX

**LocaPhone**

**About LocaPhone VoIP PBX**

LocaPhone VoIP PBX as a software-based VoIP system delivers a number of unparalleled advantages.

Substantial cost reduction - Combined with IP telephones and DECT solutions from Gigaset PRO & others, and media gateway telephony hardware offered by different manufacturers, LocaPhone VoIP PBX provides a fully featured PBX system at a fraction of the price of traditional PBX systems, while providing a level of functionality exceeding that of many of the most expensive systems available.

No licensing scheme, no limitations on functions and users, and no proprietary hardware (multiple vendors possible) is used.

Because of its "open" nature LocaPhone VoIP PBX eliminates further vendor lock-in and offers a choice to the customer to use the desired or necessary telephony hardware for its exact setting.

More information on http://www.locaphone.de

**Tested on LocaPhone VoIP PBX version : 5.3.1-xenial1**

See below for a list with supported features when using the Gigaset PRO IP Devices with LocaPhone VoIP PBX.



| Feature | ~~DE310~~ ~~DE410~~ EOL | ~~DE700~~ ~~DE900~~ EOL | Maxwell Basic/2 /3 | N510 IP PRO | N720 IP PRO | N870 IP PRO N670 IP PRO |
|---|---|---|---|---|---|---|
| Software Release | 02.00.05 | 02.00.08 | 02.25.60 | 00042.25000.0 | 00070.11300.0 | 00002.20.00000 |
| Basic Call | Yes | Yes | Yes | Yes | Yes | Yes |
| Calling line (CLIP) | Yes | Yes | Yes | Yes | Yes | Yes |
| Connected line (COLP) | Yes | Yes | Yes | Yes | Yes | Yes |
| Anonymous call (*31) | Yes | Yes | Yes | Yes | Yes | Yes |
| Do Not Disturb | Yes | Yes | Yes | Yes(5) | Yes(5) | Yes(5) |
| Message waiting | Yes | Yes | Yes | Yes | Yes | Yes |
| Call list/history | Yes(1) | Yes(1) | Yes | Yes | Yes | Yes |
| Voice mail deposit/retrieval | Yes | Yes | Yes | Yes | Yes | Yes |
| Call waiting | Yes(2) | Yes(2) | Yes(2) | Yes(2) | Yes(2) | Yes(2) |
| Call Hold / Toggle | Yes | Yes | Yes | Yes | Yes | Yes |
| Call forward (CFU) | Yes(3) | Yes(3) | Yes(3) | Yes(3) | Yes(3) | Yes(3) |
| Call forward (CFNR) | Yes(3) | Yes(3) | Yes(3) | Yes(3) | Yes(3) | Yes(3) |
| Call forward (CFB) | Yes(3) | Yes(3) | Yes(3) | Yes(3) | Yes(3) | Yes(3) |
| Call Transfer attended | Yes | Yes | Yes | Yes | Yes | Yes |
| Call Transfer unattended | Yes | Yes | Yes | Yes | Yes | Yes |
| DTMF (RFC2833) | Yes | Yes | Yes | Yes | Yes | Yes |
| Conference 3pty | Yes | Yes | Yes | Yes | No | Yes |
| BLF Busy / Idle indication | Yes | Yes | Yes | N/A | N/A | N/A |
| Call pick-up direct (*81) | Yes | Yes | Yes | Yes | Yes | Yes |
| Call pick-up group (*8) | No | No | Yes | Yes | Yes | Yes |
| Call pick-up BLF | Yes | Yes | Yes | N/A | N/A | N/A |
| Call completed elsewhere | No(4) | No(4) | No(4) | No(4) | No(4) | No(4) |
| Auto provisioning | Yes | Yes | Yes | Yes | Yes | Yes |
| Auto firmware update | Yes | Yes | Yes | Yes | Yes | Yes |

(1) Does not show the usual missed call icon on display, instead MWI will blink. Pressing the MWI button will show the missed call list.

(2) Call waiting status can not be changed via the phone menu. Instead *92 can be used to activate call waiting and ***** 92* can be used to disable call waiting.

(3) Could not be configured via the phone menu but can be configured on the platform.

(4) Platform does not send call completed elsewhere. However the provisioned phones(DExxx models) did not show a missed call.

(5) 'do not disturb' status can not be changed via the phone menu. Instead a PBX Web-UI setting or feature code

( '*93' to activate call waiting, '* 93*' disable call waiting) can be used.

** When a call has been on hold for about 3 minutes and 30 seconds the platform disconnects both users.

Full list of available feature codes.