N720 - LDAP

Below is an Auto provisioning example how to configure LDAP on the N720

LDAP provisioning example

```
<!-- LDAP -->
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].aucDirName[%]" class="symb_item" value="'Phonebook'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].aucUsername[%]" class="symb_item" value=""""/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].aucPassword[%]" class="symb_item" value=""""/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].aucServerURL[%]" class="symb_item" value="'192.168.178.26'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].uiServerPort" class="symb_item" value="389"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].aucBaseDN[%]" class="symb_item" value="'dc=pbx,dc=com'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].uiMaxNrOfSessions" class="symb_item" value="30"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].uiMaxNrOfSearchEntries" class="symb_item" value="50"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].NameFilter[%]" class="symb_item" value="'(|(cn=%)(sn=%))'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].NumberFilter[%]" class="symb_item" value="'(|(telephoneNumber=%)(mobile=%))'"
/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].NameAttributes[%]" class="symb_item" value="'displayName'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].DisplayName[%]" class="symb_item" value="'%sn, %givenName'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].bUseIndividualCredentials" class="symb_item" value="0x0"/>

<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[0].aucItemAttribute[0]" class="symb_item" value="'givenNa
me'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[1].aucItemAttribute[0]" class="symb_item" value="'sn'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[2].aucItemAttribute[0]" class="symb_item" value="'homePh
one'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[3].aucItemAttribute[0]" class="symb_item" value="'telephon
eNumber'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[4].aucItemAttribute[0]" class="symb_item" value="'mobile'"
/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[5].aucItemAttribute[0]" class="symb_item" value="'mail'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[6].aucItemAttribute[0]" class="symb_item" value="'none'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[7].aucItemAttribute[0]" class="symb_item" value="'departm
entNumber'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[8].aucItemAttribute[0]" class="symb_item" value="'none'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[9].aucItemAttribute[0]" class="symb_item" value="'none'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[10].aucItemAttribute[0]" class="symb_item" value="'none'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[11].aucItemAttribute[0]" class="symb_item" value="'none'"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[12].aucItemAttribute[0]" class="symb_item" value="'none'"/>

<SYMB_ITEM ID="BS_XML_Netdirs.aucActivatedNetdirs[0]" class="symb_item" value="0xa,0x0,"/>
<SYMB_ITEM ID="BS_XML_Netdirs.aucNetdirSelForIntKey[%]" class="symb_item" value="0xa"/>

 <!-- How to enable autolookup for incoming call -->

<SYMB_ITEM ID="BS_XML_Netdirs.aucNetdirSelForAutoLookup[0]" class="symb_item" value="0xa"/>



<!-- How to change the LDAP Cache Size the default setting is below, we cache 100 entries. You could change it to a lower value in case you
want that less entries are cached.



<SYMB_ITEM ID="BS_XML_Netdirs.stAutolookup.uiCacheSize" class="symb_item" value="0x64"/> -->
```