

# FAQ N510 Registration of Polycom DECT Soundstation



**You can register other GAP conform DECT Portable Part on N510IP PRO with their own specific registration procedure.**

To start the registration for other devices on a N510IP base station

- **press the Registration Button in front of base for approx. 3seconds**

or use the Web configurator of N510IP:

- **Settings -> Management -> Miscellaneous-> Start Registration**

The screenshot shows the web configurator interface for a Gigaset N510 IP PRO. The top navigation bar includes 'Home', 'Settings', and 'Status', with a 'Log Off' link on the right. A left sidebar lists various settings categories: Network, Telephony, Messaging, Directories, Management, Date & Time, Local Settings, Miscellaneous (highlighted in orange), Reboot & Reset, Save & Restore, and Firmware Update. The main content area is titled 'Register new handsets' and contains several options: 'Switch to handset registration mode:' with a 'Start Registration' button; 'Eco Mode' with a checkbox and description; 'Eco Mode+' with a checkbox and description; 'Change system PIN of base station' with a 'New PIN:' input field; 'LED signalling on base station'; 'Signal Ethernet Connection and Traffic:' with radio buttons for 'Yes' and 'No'; and 'VoIP Status' with a 'Show VoIP status on handset:' option and radio buttons for 'Yes' and 'No'. At the bottom right are 'Set' and 'Cancel' buttons.

**Please note:** All base connections are assigned to a Portable Part as receive connections directly after registration is complete. The first configured VoIP connection is assigned to the Portable Part as a send connection.

To find out The Registration procedures of other conforming DECT Portable Parts (PP) please look into their user manuals.

**As an example the registration procedure of an conference phone (PP) POLYCOM Soundstation 2W**

- Go to the menu and navigate to 'Admin Setup -> Diagnostics -> Restore Defaults' and press the 'OK' soft button. It will work instantaneously, then navigate down to 'Reboot Phone' and press the 'Reboot' soft button. Your phone will reboot.
- Go to the menu and navigate to 'Admin Setup -> Registration' and follow the steps carefully.

- choose the connection protocol **GAP** and press 'OK'