Interop T300/T500 Telfort

Telfort ISP

Feature	
Outgoing Calls	Yes
Incoming Calls	Yes
CLIP incoming	Yes
CLIP outgoing	Yes
Call Forwarding	Yes
Call Transfer	Yes
Call Waiting	Yes
DTMF	Yes
Anonymous Call	Yes
A-number forwarding	No

- Telfort ISP
  - Gigaset T300/T500 settings.
    - Provider settings:
    - Number Area settings:
    - Extended settings:

Gigaset T300/T500 settings.

In the Gigaset PBX go to "Configuration" - "Lines" - "Lines" and click on: **New Line**

Provider settings:

Give the Line an unique name, insert the Registration user name and Password.

In the Provider pull-down list, select "new.."



Number Area settings:

Just add the telephone numbers for this SIP trunk. The Country Code and Area Code can be filled in, if different than the default setting.



Extended settings:

To enable incoming calls, you need to use the settings below.

Open the Manual Configuration and change the default settings like in the example below. Do not forget to enable the check-box Active.



You can copy the text below to paste into the field.

```
[Telfort-incoming]

exten => _.,1,Set(channelname=Telfort-incoming)
exten => _.,2,Set(lineconfigid=1748)
exten => _.,3,Set(var_to=${SIP_HEADER(To)})
exten => _.,4,Set(firstcut=${CUT(var_to,:,2)})
exten => _.,5,Set(secoundcut=${CUT(firstcut,@,1)})
exten => _.,6,Set(CALLERID(all)=+${CALLERID(number)})
exten => _.,7,Goto(Telfort-incoming-manuell,${secoundcut},1)

[Telfort-incoming-manuell]

exten => _X.,1,Goto(incoming,${secoundcut},1)
exten => _+X.,1,Goto(incoming,${secoundcut},1)
```