

N720 - LDAP

Below is an Auto provisioning example how to configure LDAP on the N720



LDAP provisioning example

```
<!-- LDAP -->
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].aucDirName[%]" class="symb_item" value="Phonebook"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].aucUsername[%]" class="symb_item" value=""/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].aucPassword[%]" class="symb_item" value=""/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].aucServerURL[%]" class="symb_item" value="192.168.178.26"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].uiServerPort" class="symb_item" value="389"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].aucBaseDN[%]" class="symb_item" value="dc=pbx,dc=com"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].uiMaxNrOfSessions" class="symb_item" value="30"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].uiMaxNrOfSearchEntries" class="symb_item" value="50"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].NameFilter[%]" class="symb_item" value="((cn=%)(sn=%))"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].NumberFilter[%]" class="symb_item" value="((telephoneNumber=%)(mobile=%))"/>
/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].NameAttributes[%]" class="symb_item" value="displayName"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].DisplayName[%]" class="symb_item" value="%sn, %givenName"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].bUseIndividualCredentials" class="symb_item" value="0x0"/>

<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[0].aucItemAttribute[0]" class="symb_item" value="givenName"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[1].aucItemAttribute[0]" class="symb_item" value="sn"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[2].aucItemAttribute[0]" class="symb_item" value="homePhone"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[3].aucItemAttribute[0]" class="symb_item" value="telephoneNumber"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[4].aucItemAttribute[0]" class="symb_item" value="mobile"/>
/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[5].aucItemAttribute[0]" class="symb_item" value="mail"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[6].aucItemAttribute[0]" class="symb_item" value="none"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[7].aucItemAttribute[0]" class="symb_item" value="departmentNumber"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[8].aucItemAttribute[0]" class="symb_item" value="none"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[9].aucItemAttribute[0]" class="symb_item" value="none"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[10].aucItemAttribute[0]" class="symb_item" value="none"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[11].aucItemAttribute[0]" class="symb_item" value="none"/>
<SYMB_ITEM ID="BS_LDAP_Netdirs.astNetdirProvider[%].astNetDirDirectoryItems[12].aucItemAttribute[0]" class="symb_item" value="none"/>

<SYMB_ITEM ID="BS_XML_Netdirs.aucActivatedNetdirs[0]" class="symb_item" value="0xa,0x0,"/>
<SYMB_ITEM ID="BS_XML_Netdirs.aucNetdirSelForIntKey[%]" class="symb_item" value="0xa"/>

<!-- How to enable autolookup for incoming call -->

<SYMB_ITEM ID="BS_XML_Netdirs.aucNetdirSelForAutoLookup[0]" class="symb_item" value="0xa"/>

<!-- How to change the LDAP Cache Size the default setting is below, we cache 100 entries. You could change it to a lower value in case you want that less entries are cached.

<SYMB_ITEM ID="BS_XML_Netdirs.stAutolookup.uiCacheSize" class="symb_item" value="0x64"/> -->
```