

LDAP Provisioning Parameter - N510 IP PRO

This is list of fields used to store LDAP attributes (with default values) needed for provisioning:

```
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[0].aucItemAttribute[0]="givenName"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[1].aucItemAttribute[0]="sn"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[2].aucItemAttribute[0]="homePhone"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[3].aucItemAttribute[0]="telephoneNumber"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[4].aucItemAttribute[0]="mobile"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[5].aucItemAttribute[0]="mail"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[6].aucItemAttribute[0]="facsimileTelephoneNumber"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[7].aucItemAttribute[0]="company"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[8].aucItemAttribute[0]="street"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[9].aucItemAttribute[0]="l"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[10].aucItemAttribute[0]="postalCode"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[11].aucItemAttribute[0]="c"
BS_LDAP_Netdirs.astNetdirProvider[0].astNetDirDirectoryItems[12].aucItemAttribute[0]=""
```

Order of items is:

FIRST NAME,
LAST NAME,
PHONE HOME,
PHONE OFFICE,
PHONE MOBILE,
EMAIL,
FAX,
COMPANY,
STREET,
CITY,
ZIP,
COUNTRY,
ADDITIONAL ATTRIBUTE

For last item there's also an additional field:

```
BS_LDAP_Netdirs.astNetdirProvider[%].IsAdditionalAttributeDialable=[0|1]
```

This can be used to indicate that additional attribute should be treated as diallable number.

Enable the LDAP directory:

```
<SYMB_ITEM ID="BS_XML_Netdirs.aucActivatedNetdirs" class="symb_item" value="10"/>
```